


## AUTOMATIC TYRE CHANGER FOR PASSENGER CARS

MODEL	DESCRIPTION
<b>4RA0300</b>	Automatic Tyre Changer 3 Phase Motor up to Internal Clamping 22"
<b>4RA0305</b>	Automatic Tyre Changer 3 Phase Motor up to Internal Clamping 22" with tubeless inflating device.
<b>4RA0351</b>	Automatic Tyre Changer Single Phase Motor up to Internal Clamping 22"
<b>4RA0500</b>	Automatic Tyre Changer 3 Phase Motor up to Internal Clamping 24"

	<b>TECHNICAL SPECIFICATIONS</b>			
	<b>Model</b>	<b>4RA0300 4RA0305</b>	<b>4RA0351</b>	<b>4RA0500</b>
	Internal Clamping	12-22"		12 – 24 "
	External Clamping	10-20"		10 – 22 "
	Max Wheel Diameter	1000 mm		1060 mm
	Max Wheel Width	320 mm		370 mm
	Turntable Thickness	12 mm		
	Motor	3 Phase 0.55 Kw; 230/400 V; 50Hz	Single Phase 230V	3 Phase 1 Kw; 230/400 V; 50Hz
	Designed for	Professional Tyre Workshops		
	Main Specifications	<ul style="list-style-type: none"> <li>• High resistance vertical column with AUTOMATIC back-ward movement.</li> <li>• Two speeds turntable and pneumatic tyre placing.</li> <li>• High quality connecting rods guarantee the same tightly strength for any wheel diameter Ø</li> <li>• Manometer for inflating pressure control equipped with deflating push button.</li> <li>• Inflating nozzles for tubeless inflating from the sides.</li> <li>• Plastic protectors</li> <li>• Optional: Auxiliary Arm BP</li> </ul>		

(\* )Tire special system boiler and claws with air outlet for inflating tires fast deformed.